



## SYNMAR NUMA V32 | S400151

V170622

### Description

The Synmar Numa V32 is a high grade EP multigrade hydraulic oil based on carefully selected solvent refined base oils under addition of additives to obtain the following properties:

- a high and stable viscosity index
- excellent wear-preventing properties
- a very good activity against corrosion
- an excellent stability against oxidation
- very good demulsification properties
- very good deaerating and foam suppressing properties
- good compatibility with seals and gaskets made from synthetic material
- a low pour point

### Application

The Synmar Numa V32 is a hydraulic fluid which consists of tailormade quality for heavy duty hydraulic systems of earthmoving equipment and of permanent installations that have to work under high pressures over a wide temperature range. This fluid is **not** compatible in systems, containing parts or equipment with a silver lining.

### Performance Level

Denison HF-0, HF-2  
DIN 51524 Part III HVLP  
ISO 11158 Type HV  
ISO 6743-4 Type HV

### Typicals

Density at 15 °C, kg/l	0,852
Viscosity 40 °C, mm <sup>2</sup> /s	32,00
Viscosity 100 °C, mm <sup>2</sup> /s	6,44
Viscosity Index	159
Flash Point COC, °C	190
Pour Point, °C	-39
Acid number, mgKOH/g	0,40
Sulphate Ash, %	0,06